

## LOW PRESSURE FUEL HOSE - UNREINFORCED

### SUITABILITY

|  |       |
|--|-------|
| • Engine lubricating oils                      | 80°C  |
| • Hydraulic fluids on mineral & glycol base    | 80°C  |
| • Diesel fuels                                 | 80°C  |
| • Fuel oil EL & L                              | 70°C  |
| • Herbal greases air                           | 80°C  |
| • Oil containing air                           | 80°C  |
| • Cooling materials (glycol, glysantin, etc.)  | 80°C  |
| • Water  | 80°C  |
| • Watery solutions without oxidising materials | 80°C  |
| Resistance to cold                             | -35°C |

### MATERIALS

|              |                  |
|--------------|------------------|
| Construction | Synthetic rubber |
|--------------|------------------|

New

### CONICAL HOSETAIL FOR USE WITH UNION NUT



4700

| PART NUMBER | HOSE ID | UNION NUT |
|-------------|---------|-----------|
| S203-602    | 4.5 mm  | 1/8" BSPP |
| S203-604    | 5.5 mm  | 1/4" BSPP |
| S203-606    | 7.5 mm  | 1/4" BSPP |
| S203-608    | 9.0 mm  | 3/8" BSPP |
| S203-610    | 11.0 mm | 1/2" BSPP |
| S203-612    | 14.0 mm | 1/2" BSPP |
| S203-616    | 17.0 mm | 3/4" BSPP |
| S203-620    | 21.5 mm | 1" BSPP   |

New

### LOW PRESSURE FUEL HOSE



4700

#### PART NUMBER

| PART NUMBER |      |      |
|-------------|------|------|
| S601-202    | 4.8  | 8.8  |
| S601-204    | 6.0  | 10.0 |
| S601-206    | 8.0  | 12.0 |
| S601-208    | 9.5  | 13.5 |
| S601-210    | 11.5 | 17.0 |
| S601-213    | 14.5 | 20.5 |
| S601-216    | 17.5 | 24.5 |
| S601-220    | 22.0 | 30.0 |

New

### UNION NUT IMPERIAL




4700

#### PART NUMBER

| PART NUMBER | THREAD    | FOR USE WITH |
|-------------|-----------|--------------|
| S203-902    | 1/8" BSPP | S203-602     |
| S203-904    | 1/4" BSPP | S203-604     |
| S203-906    | 1/4" BSPP | S203-606     |
| S203-908    | 3/8" BSPP | S203-608     |
| S203-910    | 1/2" BSPP | S203-610     |
| S203-912    | 1/2" BSPP | S203-612     |
| S203-916    | 3/4" BSPP | S203-616     |
| S203-920    | 1 BSPP    | S203-620     |

### FERRULE STEEL



4700

| PART NUMBER | FERRULE ID | D2      | LENGTH  |
|-------------|------------|---------|---------|
| S204-010    | 10.5 mm    | 6.2 mm  | 15.0 mm |
| S204-011    | 11.5 mm    | 7.3 mm  | 15.0 mm |
| S204-012    | 12.5 mm    | 7.3 mm  | 20.0 mm |
| S204-013    | 13.5 mm    | 9.3 mm  | 20.0 mm |
| S204-014    | 14.5 mm    | 9.3 mm  | 20.0 mm |
| S204-015    | 15.5 mm    | 11.3 mm | 20.0 mm |
| S204-016    | 16.0 mm    | 11.3 mm | 20.0 mm |
| S204-017    | 17.0 mm    | 11.3 mm | 21.0 mm |
| S204-018    | 18.0 mm    | 13.4 mm | 21.0 mm |
| S204-019    | 19.0 mm    | 13.4 mm | 21.0 mm |
| S204-020    | 20.0 mm    | 13.4 mm | 20.0 mm |
| S204-022    | 22.0 mm    | 16.9 mm | 31.0 mm |
| S204-023    | 23.0 mm    | 16.9 mm | 32.0 mm |
| S204-024    | 24.5 mm    | 16.9 mm | 32.0 mm |
| S204-026    | 26.5 mm    | 16.9 mm | 32.0 mm |
| S204-028    | 28.0 mm    | 19.5 mm | 32.0 mm |
| S204-030    | 30.5 mm    | 23.7 mm | 32.0 mm |

### CRIMPING TOOL ARNSTEN



4700

#### PART NUMBER

| PART NUMBER | DESCRIPTION                           |
|-------------|---------------------------------------|
| S209-001    | To suit nominal bore of 2 mm to 13 mm |

NOTE: This crimping tool is supplied with 2 sets of crimping dies, 2 – 8 mm & 10 – 13 mm hose bore. Six clamping dies guarantee an immaculate press fit while the crimping tool is bench vice mounted.

New

### STANDPIPE HOSETAIL



4700

| PART NUMBER | HOSE ID | STANDPIPE OD |
|-------------|---------|--------------|
| S203-304    | 4.5 mm  | 4 mm         |
| S203-306    | 5.5 mm  | 6 mm         |
| S203-308    | 7.5 mm  | 8 mm         |
| S203-310    | 9.0 mm  | 10 mm        |
| S203-312    | 11.0 mm | 12 mm        |
| S203-315    | 14.0 mm | 15 mm        |
| S203-318    | 17.0 mm | 18 mm        |
| S203-322    | 21.5 mm | 22 mm        |

New

### COPPER WASHER STANDARD TYPE



4700

#### PART NUMBER

| PART NUMBER | SIZE          |
|-------------|---------------|
| S100-505    | 6 mm x 10 mm  |
| S100-517    | 8 mm x 14 mm  |
| S100-531    | 10 mm x 14 mm |
| S100-536    | 10 mm x 16 mm |
| S100-547    | 12 mm x 16 mm |
| S100-587    | 16 mm x 22 mm |
| S100-597    | 18 mm x 22 mm |
| S100-608    | 20 mm x 24 mm |
| S100-627    | 22 mm x 27 mm |
| S100-662    | 30 mm x 36 mm |