




FEATURES		BENEFITS	
<ul style="list-style-type: none"> Vented safety function Extremely high flow capacity Compact design Pre-applied sealant on male threads Smaller outside dimension than comparable designs 		<ul style="list-style-type: none"> Easy to handle One hand operation Fully automatic operation Extremely energy efficient 	
SPECIFICATIONS			
Nominal flow diameter	7.6 mm (5/16")		
Flow capacity	2250 l/min (79.4 CFM)*		
Max. working pressure	16 bar (232 psi)		
Min. burst pressure	140 bar (2030 psi)		
Connection force	86 N		
Temperature range	-20°C to +100°C (-4°F to +212°F)		
Coupling material	Zinc plated steel / brass		
Coupling seal material	NBR		
Nipple material	Hardened zinc plated steel		



Not actual size

Single Shut-off

Interchange

CEJN Original,
Eurostandard, Series 25

***High flow capacity**
*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

NPT threads are available



eSAFE VENTED SAFETY COUPLINGS

**320 SERIES
HOSE BARB**



PART NUMBER	TUBE ID	METRIC EQ.
C103202002	1/4"	6 mm
C103202003	5/16"	8 mm
C103202009	11/32"	9 mm
C103202004	3/8"	10 mm
C103202005	1/2"	13 mm

**320 SERIES
STREAMLINE CONNECTION**



PART NUMBER	TUBE OD	TUBE ID
C103202058	8.0 mm	5.0 mm
C103202060	10.0 mm	6.5 mm
C103202062	12.0 mm	8.0 mm
C103202063	13.5 mm	9.5 mm
C103202066	16.0 mm	11.0 mm
C103202068	18.0 mm	13.0 mm

**320 SERIES
BSPT MALE
WITH LOCTITE DRY-SEAL®**



PART NUMBER	THREAD
C103202152	1/4" BSPT
C103202154	3/8" BSPT
C103202155	1/2" BSPT

**320 SERIES
STREAMLINE CONNECTION
WITH LOCK RING**



PART NUMBER	TUBE OD	TUBE ID
C103202090	10.0 mm	6.5 mm
C103202092	12.0 mm	8.0 mm
C103202096	16.0 mm	11.0 mm

**320 SERIES
BSPP FEMALE**



PART NUMBER	THREAD
C103202202	1/4" BSPP
C103202204	3/8" BSPP
C103202205	1/2" BSPP

**320 SERIES
SOFT-LINE CONNECTION**



PART NUMBER	TUBE OD	TUBE ID
C103202082	12.0 mm	8.0 mm
C103202083	13.5 mm	9.5 mm
C103202085	16.0 mm	11.0 mm
C103202088	18.0 mm	13.0 mm

**320 SERIES
BSPP FEMALE
WITH LOCK RING**



PART NUMBER	THREAD
C103202244	3/8" BSPP



Did you know?

Products with safety benefits are indicated by a chevron at the bottom of their table