

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name or designation of the mixture** INDUSTRIAL DEGREASER FG

**Registration number** -

**Synonyms** None.

**Product code** BDS000272AE

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Cleaners - Heavy duty

**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

**Company name** CRC Industries UK Ltd.  
**Address** Wylds Road  
 Castlefield Industrial Estate  
 TA6 4DD Bridgwater Somerset  
 United Kingdom  
**Telephone** +44 1278 727200  
**Fax** +44 1278 425644  
**E-mail** hse.uk@crcind.com  
**Website** www.crcind.com

**Company name** CRC Industries Europe bv  
**Address** Touwslagerstraat 1  
 9240 Zele  
 Belgium  
**Telephone** +32(0)52/45.60.11  
**Fax** +32(0)52/45.00.34  
**E-mail** hse@crcind.com  
**Website** www.crcind.com

**1.4. Emergency telephone number** Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

**General in EU** 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Austria National Poisons Information Centre** +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Belgium National Poisons Control Center** 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Bulgaria National Toxicological Information Centre** +359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Czech Republic National Poisons Information Centre** +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

**Denmark National Poisons Control Center** +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Estonia National Poisons Information Centre** 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)

**Finland National Poison Information Center** (09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

<b>France National Poisons Control Center</b>	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Hungary National Emergency Phone Number</b>	36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Lithuania Neatidėliotina informacija apsinuodijus</b>	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Malta Accident and Emergency Department</b>	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Netherlands National Poisons Information Center (NVIC)</b>	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
<b>Norway Norwegian Poison Information Center</b>	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Portugal Poison Centre</b>	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Romania Număr de telefon care poate fi apelat în caz de urgență:</b>	021 5992300, int. 291 Spitalul Clinic de Urgență București: spital@urgentaflorasca.ro
<b>Romania</b>	0265 212111, 0265 211292, 0265 217235 Spitalul Clinic Județean de Urgență Târgu Mureș: secretariat@spitjudms.ro
<b>Slovakia National Toxicological Information Centre</b>	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Sweden National Poison Information Center</b>	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Switzerland Tox Info Suisse</b>	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture


The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

<b>Physical hazards</b>		
Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
<b>Health hazards</b>		
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

<b>Contains:</b>	2-Methoxy-1-methylethyl acetate, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
<b>Hazard pictograms</b>	
<b>Signal word</b>	Danger
<b>Hazard statements</b>	
H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H336	May cause drowsiness or dizziness.

#### Precautionary statements

<b>Prevention</b>	
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing mist/vapours.  
P271 Use only outdoors or in a well-ventilated area.

**Response** Not assigned.

**Storage**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal**

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Supplemental label information**

EUH066 - Repeated exposure may cause skin dryness or cracking.  
Regulation (EC) No 648/2004 on detergents: aliphatic hydrocarbons > 30 %

**2.3. Other hazards**

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	50 - 75	EC919-857-5 919-857-5	01-2119463258-33	-	
<b>Classification:</b> Flam. Liq. 3;H226, STOT SE 3;H336, Asp. Tox. 1;H304					
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER	10 - 25	107-98-2 203-539-1	01-2119457435-35	603-064-00-3	#
<b>Classification:</b> Flam. Liq. 3;H226, STOT SE 3;H336					
2-Methoxy-1-methylethyl acetate	10 - 25	108-65-6 203-603-9	-	607-195-00-7	#
<b>Classification:</b> Flam. Liq. 3;H226, STOT SE 3;H336					
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
<b>Classification:</b> Press. Gas;H280					
Butan-2-ol	<5	78-92-2 201-158-5	01-2119475146-36	603-127-00-5	
<b>Classification:</b> Flam. Liq. 3;H226, Eye Irrit. 2;H319, STOT SE 3;H335;H336					

**List of abbreviations and symbols that may be used above**

#: This substance has been assigned Union workplace exposure limit(s).  
ATE: Acute toxicity estimate.  
M: M-factor  
PBT: persistent, bioaccumulative and toxic substance.  
vPvB: very persistent and very bioaccumulative substance.  
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

**SECTION 4: First aid measures**

**General information**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

**4.1. Description of first aid measures**

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.  
**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.  
**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.  
**Ingestion** In the unlikely event of swallowing contact a physician or poison control centre.

**4.2. Most important symptoms and effects, both acute and delayed**

May cause drowsiness or dizziness. Headache. Nausea, vomiting.

**4.3. Indication of any immediate medical attention and special treatment needed**

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

<b>General fire hazards</b>	Extremely flammable aerosol.
<b>5.1. Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>5.2. Special hazards arising from the substance or mixture</b>	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Special fire fighting procedures</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
<b>For emergency responders</b>	Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>6.2. Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.
<b>6.3. Methods and material for containment and cleaning up</b>	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
<b>6.4. Reference to other sections</b>	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)
<b>7.3. Specific end use(s)</b>	Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Ceiling	187 mg/m3
		50 ppm
	MAK	187 mg/m3
		50 ppm

**Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001**

<b>Components</b>	<b>Type</b>	<b>Value</b>
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Ceiling	550 mg/m3
		100 ppm
	MAK	275 mg/m3
Butan-2-ol (CAS 78-92-2)		50 ppm
	MAK	150 mg/m3
	STEL	600 mg/m3
Carbon dioxide (CAS 124-38-9)		200 ppm
	Ceiling	18000 mg/m3
	MAK	10000 ppm
		9000 mg/m3
		5000 ppm

**Belgium. Exposure Limit Values**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	369 mg/m3
		100 ppm
	TWA	184 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		50 ppm
	STEL	550 mg/m3
	TWA	100 ppm
Butan-2-ol (CAS 78-92-2)		275 mg/m3
		50 ppm
	TWA	307 mg/m3
Carbon dioxide (CAS 124-38-9)		100 ppm
	STEL	54784 mg/m3
	TWA	30000 ppm
		9131 mg/m3
		5000 ppm

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		100 ppm
	STEL	550 mg/m3
	TWA	100 ppm
Carbon dioxide (CAS 124-38-9)		275 mg/m3
		50 ppm
	TWA	9000 mg/m3
		5000 ppm

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	MAC	375 mg/m3
		100 ppm
	STEL	568 mg/m3 150 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	MAC	275 mg/m3
	STEL	50 ppm 550 mg/m3 100 ppm
Butan-2-ol (CAS 78-92-2)	MAC	308 mg/m3
		100 ppm
	STEL	462 mg/m3 150 ppm
Carbon dioxide (CAS 124-38-9)	MAC	9000 mg/m3
		5000 ppm

**Czech Republic. OELs. Government Decree 361**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Ceiling	550 mg/m3
	TWA	270 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Ceiling	550 mg/m3
	TWA	270 mg/m3
Butan-2-ol (CAS 78-92-2)	Ceiling	600 mg/m3
	TWA	300 mg/m3
Carbon dioxide (CAS 124-38-9)	Ceiling	45000 mg/m3
	TWA	9000 mg/m3

**Denmark**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	25 ppm

**Denmark. Exposure Limit Values**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	TLV	185 mg/m3
		50 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TLV	275 mg/m3
		50 ppm
Butan-2-ol (CAS 78-92-2)	Ceiling	150 mg/m3
		50 ppm
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3
		5000 ppm

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3 100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3 50 ppm
Butan-2-ol (CAS 78-92-2)	STEL	250 mg/m3
		75 ppm
	TWA	150 mg/m3 50 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Finland**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	500 mg/m3

**Finland. Workplace Exposure Limits**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	560 mg/m3
		150 ppm
	TWA	370 mg/m3 100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	270 mg/m3 50 ppm
Butan-2-ol (CAS 78-92-2)	STEL	230 mg/m3
		75 ppm
	TWA	150 mg/m3 50 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3
		5000 ppm

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	VLE	375 mg/m3
		100 ppm
	<b>Regulatory status:</b> Regulatory binding (VRC)	
	<b>Regulatory status:</b> Regulatory binding (VRC)	

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
	VME	188 mg/m3
<b>Regulatory status:</b>	Regulatory binding (VRC)	
		50 ppm
<b>Regulatory status:</b>	Regulatory binding (VRC)	
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	VLE	550 mg/m3
<b>Regulatory status:</b>	Regulatory binding (VRC)	
		100 ppm
<b>Regulatory status:</b>	Regulatory binding (VRC)	
	VME	275 mg/m3
<b>Regulatory status:</b>	Regulatory binding (VRC)	
		50 ppm
<b>Regulatory status:</b>	Regulatory binding (VRC)	
Butan-2-ol (CAS 78-92-2)	VME	300 mg/m3
<b>Regulatory status:</b>	Indicative limit (VL)	
		100 ppm
<b>Regulatory status:</b>	Indicative limit (VL)	
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m3
<b>Regulatory status:</b>	Regulatory indicative (VRI)	
		5000 ppm
<b>Regulatory status:</b>	Regulatory indicative (VRI)	

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	TWA	370 mg/m3
		100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	270 mg/m3
		50 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3
		5000 ppm

**Germany - TRGS 900**

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	300 mg/m3

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	AGW	370 mg/m3
		100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	AGW	270 mg/m3
		50 ppm
Carbon dioxide (CAS 124-38-9)	AGW	9100 mg/m3
		5000 ppm



**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	1080 mg/m3
		300 ppm
	TWA	360 mg/m3 100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3 50 ppm
Butan-2-ol (CAS 78-92-2)	STEL	450 mg/m3
		150 ppm
	TWA	300 mg/m3 100 ppm
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3
		5000 ppm
	TWA	9000 mg/m3 5000 ppm

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
	TWA	375 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	275 mg/m3
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	185 mg/m3 50 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3 50 ppm
Butan-2-ol (CAS 78-92-2)	STEL	150 mg/m3
		50 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Ireland. Occupational Exposure Limits**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3
Butan-2-ol (CAS 78-92-2)	STEL	450 mg/m3
		150 ppm
	TWA	300 mg/m3
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		100 ppm
		5000 ppm

**Italy. Occupational Exposure Limits**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3
Butan-2-ol (CAS 78-92-2)	TWA	100 ppm
		50 ppm
	TWA	9000 mg/m3
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		100 ppm
		5000 ppm

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3
Butan-2-ol (CAS 78-92-2)	TWA	10 mg/m3
		50 ppm
	TWA	9000 mg/m3
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		100 ppm
		5000 ppm

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value
		5000 ppm

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	300 mg/m <sup>3</sup>
		75 ppm
	TWA	190 mg/m <sup>3</sup>
		50 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	400 mg/m <sup>3</sup>
		75 ppm
	TWA	250 mg/m <sup>3</sup>
		50 ppm
Butan-2-ol (CAS 78-92-2)	STEL	250 mg/m <sup>3</sup>
		75 ppm
	TWA	150 mg/m <sup>3</sup>
		50 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m <sup>3</sup>
		150 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m <sup>3</sup>
		100 ppm

**Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m <sup>3</sup>
		150 ppm
	TWA	375 mg/m <sup>3</sup>
		100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m <sup>3</sup>
		100 ppm
	TWA	275 mg/m <sup>3</sup>
		50 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Netherlands. OELs (binding)**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	563 mg/m3
	TWA	375 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	550 mg/m3
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3

**Norway**

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	275 mg/m3

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	TLV	180 mg/m3
		50 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TLV	270 mg/m3
		50 ppm
Butan-2-ol (CAS 78-92-2)	Ceiling	75 mg/m3
		25 ppm
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3
		5000 ppm

**Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	360 mg/m3
		0 ppm
	TWA	180 mg/m3
		0 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	520 mg/m3
		0 ppm
	TWA	260 mg/m3
		0 ppm
Butan-2-ol (CAS 78-92-2)	STEL	450 mg/m3
		0 ppm
	TWA	300 mg/m3
		0 ppm
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m3
		0 ppm
	TWA	9000 mg/m3
		0 ppm

**Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3 100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3 50 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3 5000 ppm

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	100 ppm
	TWA	50 ppm
Butan-2-ol (CAS 78-92-2)	TWA	100 ppm
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3 100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3 50 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3 5000 ppm

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3
		150 ppm
	TWA	375 mg/m3 100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value
		50 ppm
Butan-2-ol (CAS 78-92-2)	TWA	310 mg/m <sup>3</sup>
		100 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	TWA	375 mg/m <sup>3</sup>
		100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	275 mg/m <sup>3</sup>
		50 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Spain. Occupational Exposure Limits**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m <sup>3</sup>
		150 ppm
	TWA	375 mg/m <sup>3</sup>
		100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	550 mg/m <sup>3</sup>
		100 ppm
	TWA	275 mg/m <sup>3</sup>
		50 ppm
Butan-2-ol (CAS 78-92-2)	TWA	308 mg/m <sup>3</sup>
		100 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9150 mg/m <sup>3</sup>
		5000 ppm

**Sweden**

Components	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	STEL (STV)	600 mg/m <sup>3</sup>
	TWA	300 mg/m <sup>3</sup>

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Ceiling	568 mg/m <sup>3</sup>
		150 ppm
	STEL	300 mg/m <sup>3</sup>
		75 ppm
	TWA	190 mg/m <sup>3</sup>

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Ceiling	50 ppm 550 mg/m3
	TWA	100 ppm 275 mg/m3
Butan-2-ol (CAS 78-92-2)	STEL	50 ppm 250 mg/m3
	TWA	75 ppm 150 mg/m3
Carbon dioxide (CAS 124-38-9)	STEL	50 ppm 18000 mg/m3
	TWA	10000 ppm 9000 mg/m3 5000 ppm

**Switzerland  
Components**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	STEL	6000 mg/m3
	TWA	300 mg/m3

**Switzerland. SUVA Grenzwerte am Arbeitsplatz  
Components**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	720 mg/m3
	TWA	200 ppm 360 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	100 ppm 275 mg/m3
	TWA	50 ppm 275 mg/m3
Butan-2-ol (CAS 78-92-2)	STEL	50 ppm 600 mg/m3
	TWA	200 ppm 300 mg/m3
Carbon dioxide (CAS 124-38-9)	TWA	100 ppm 9000 mg/m3 5000 ppm

**UK. EH40 Workplace Exposure Limits (WELs)  
Components**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	560 mg/m3
	TWA	150 ppm 375 mg/m3
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	100 ppm 548 mg/m3
		100 ppm

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value
Butan-2-ol (CAS 78-92-2)	TWA	274 mg/m3 50 ppm
	STEL	462 mg/m3 150 ppm
	TWA	308 mg/m3 100 ppm
	STEL	27400 mg/m3 15000 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9150 mg/m3 5000 ppm

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU**

Components	Type	Value
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	568 mg/m3 150 ppm
	TWA	375 mg/m3 100 ppm
	STEL	550 mg/m3 100 ppm
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	275 mg/m3 50 ppm
	TWA	9000 mg/m3 5000 ppm

**Biological limit values****Germany. TRGS 903, BAT List (Biological Limit Values)**

Components	Value	Determinant	Specimen	Sampling Time
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	15 mg/l	1-Methoxypropan-2-ol	Urine	*

\* - For sampling details, please see the source document.

**Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)**

Components	Value	Determinant	Specimen	Sampling Time
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	20 mg/l	1-METHOXYPROPANOL-2	Urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)****General Population**

Components	Value	Assessment factor	Notes
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)			
Long-term, Systemic, Dermal	78 mg/kg bw/day	16,8	Repeated dose toxicity
Long-term, Systemic, Inhalation	43,9 mg/m3		Repeated dose toxicity
Long-term, Systemic, Oral	33 mg/kg bw/day	28	Repeated dose toxicity
Butan-2-ol (CAS 78-92-2)			
Long-term, Systemic, Dermal	203 mg/kg bw/day	100	Repeated dose toxicity
Long-term, Systemic, Inhalation	213 mg/m3		Repeated dose toxicity



Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS EC919-857-5)

Long-term, Systemic, Dermal	300 mg/kg
Long-term, Systemic, Inhalation	900 mg/m <sup>3</sup>
Long-term, Systemic, Oral	300 mg/kg

### Workers

Components	Value	Assessment factor	Notes
<b>1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)</b>			
Long-term, Systemic, Dermal	183 mg/kg bw/day	10,08	Repeated dose toxicity
Long-term, Systemic, Inhalation	369 mg/m <sup>3</sup>		Repeated dose toxicity
Short-term, Local, Inhalation	553,5 mg/m <sup>3</sup>		Neurotoxicity
Short-term, Systemic, Inhalation	553,5 mg/m <sup>3</sup>		Neurotoxicity
<b>Butan-2-ol (CAS 78-92-2)</b>			
Long-term, Systemic, Dermal	405 mg/kg bw/day	50	Repeated dose toxicity
Long-term, Systemic, Inhalation	600 mg/m <sup>3</sup>		Repeated dose toxicity
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics (CAS EC919-857-5)</b>			
Long-term, Systemic, Dermal	300 mg/kg		
Short-term, Systemic, Inhalation	1500 mg/m <sup>3</sup>		

### Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
<b>1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)</b>			
Freshwater	10 mg/l	100	
Sediment (freshwater)	52,3 mg/kg		
Soil	4,59 mg/kg		
STP	100 mg/l	10	
<b>Butan-2-ol (CAS 78-92-2)</b>			
Freshwater	47,1 mg/l	1	
Sediment (freshwater)	196,19 mg/kg		
Soil	11,58 mg/kg	1	
STP	761 mg/l	1	

### Exposure guidelines

#### Austria MAK: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

#### Belgium OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

#### Bulgaria OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

#### Croatia ELVs: Skin designation

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
--	-----------------------------------

#### Czech Republic PELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

#### Denmark GV: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Butan-2-ol (CAS 78-92-2)	Can be absorbed through the skin.

#### Estonia OELs: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Butan-2-ol (CAS 78-92-2)	Can be absorbed through the skin.

#### EU Exposure Limit Values: Skin designation

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

**Finland Exposure Limit Values: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Butan-2-ol (CAS 78-92-2)	Can be absorbed through the skin.

**France INRS: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

**Greece OEL: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

**Hungary OELs: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
--	-----------------------------------

**Iceland OELs: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Butan-2-ol (CAS 78-92-2)	Can be absorbed through the skin.

**Ireland Exposure Limit Values: Skin designation**

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
--	-----------------------------------

**Italy OELs: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Danger of cutaneous absorption
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Danger of cutaneous absorption

**Latvia OELs: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

**Lithuania OELs: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Butan-2-ol (CAS 78-92-2)	Can be absorbed through the skin.

**Luxembourg OELs: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

**Malta OELs: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

**Netherlands OELs (binding): Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
--	-----------------------------------

**Norway Exposure Limit Values: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Butan-2-ol (CAS 78-92-2)	Can be absorbed through the skin.

**Portugal OELs: Skin designation**

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
--	-----------------------------------

**Romania OELs: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

**Slovakia OELs: Skin designation**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
--	-----------------------------------

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
<b>Spain OELs: Skin designation</b>	
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
<b>Sweden Threshold Limit Values: Skin designation</b>	
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Butan-2-ol (CAS 78-92-2)	Can be absorbed through the skin.
<b>UK EH40 WEL: Skin designation</b>	
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.

## 8.2. Exposure controls

**Appropriate engineering controls** Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

<b>General information</b>	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.
<b>Skin protection</b>	
- <b>Hand protection</b>	When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.
- <b>Other</b>	Not available.
<b>Respiratory protection</b>	In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type A)
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Environmental exposure controls** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol.
<b>Colour</b>	Colourless.
<b>Odour</b>	Sweet ether-like.
<b>Melting point/freezing point</b>	-114 °C (-173,2 °F) estimated
<b>Boiling point or initial boiling point and boiling range</b>	100 - 200 °C (212 - 392 °F)
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	0,6 % estimated
<b>Explosive limit – upper (%)</b>	9,8 % estimated
<b>Flash point</b>	23,0 °C (73,4 °F) Closed cup
<b>Auto-ignition temperature</b>	> 200 °C (> 392 °F)
<b>Decomposition temperature</b>	Not available.
<b>pH</b>	Not applicable.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.

<b>Solubility (other)</b>	Insoluble in water
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	0,81
<b>Particle characteristics</b>	Not available.

## 9.2. Other information

**9.2.1. Information with regard to physical hazard classes** No relevant additional information available.

### 9.2.2. Other safety characteristics

#### Aerosol spray enclosed space

**Deflagration density** Not available.

**Aerosol spray ignition distance** Not available.

**Chemical family** Cleaner

**Density** 0,81 g/cm<sup>3</sup>

**Evaporation rate** Not available.

**Explosive properties** Not explosive.

**Heat of combustion** 33,9 kJ/g

**Oxidising properties** Not oxidising.

**VOC** 783 g/l

## SECTION 10: Stability and reactivity

**10.1. Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability** Material is stable under normal conditions.

**10.3. Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.

**10.4. Conditions to avoid** Avoid high temperatures.

**10.5. Incompatible materials** Strong acids.

**10.6. Hazardous decomposition products** Carbon oxides.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

**Inhalation** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

**Skin contact** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms** May cause drowsiness or dizziness. Headache. Nausea, vomiting.

### 11.1. Information on toxicological effects

**Acute toxicity** Based on available data, the classification criteria are not met.

Components	Species	Test Results
------------	---------	--------------

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)

#### Acute

##### **Dermal**

LD50	Rabbit	13 g/kg
------	--------	---------

##### **Inhalation**

LC50	Rat	54,6 mg/l, 4 Hours
------	-----	--------------------

##### **Oral**

LD50	Rat	5,71 g/kg
------	-----	-----------

Components	Species	Test Results
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		
<b>Acute</b>		
<b>Dermal</b>		
LC50	Rabbit	> 5000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Butan-2-ol (CAS 78-92-2)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 5000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.	
<b>Serious eye damage/eye irritation</b>	Based on available data, the classification criteria are not met.	
<b>Respiratory sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Skin sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.	
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.	
<b>Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)</b>		
Not listed.		
<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness or dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	Based on available data, the classification criteria are not met.	
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met.	
<b>Mixture versus substance information</b>	Not available.	
<b>11.2. Information on other hazards</b>		
<b>Endocrine disrupting properties</b>	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	
<b>Other information</b>	Not available.	

## SECTION 12: Ecological information

**12.1. Toxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)		
<b>Aquatic</b>		
<i>Acute</i>		
Algae	EC50	Algae > 1000 mg/l, 72 h
Crustacea	EC50	Daphnia > 1000 mg/l, 48 h
Fish	LC50	Oncorhynchus mykiss > 1000 mg/l, 96 h
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		
<b>Aquatic</b>		
<i>Acute</i>		
Algae	EC50	Algae > 1000 mg/l, 72 h
Crustacea	EC50	Daphnia > 400 mg/l, 48 h

Components	Species	Test Results
Butan-2-ol (CAS 78-92-2)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) >= 1859 - <= 7143 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) >= 3380 - <= 3990 mg/l, 96 hours
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
<i>Acute</i>		
Other	LC50	Pseudokirchnerella subcapitata > 1000 mg/l, 72 h
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Oncorhynchus mykiss > 1000 mg/l
<b>12.2. Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.	
<b>12.3. Bioaccumulative potential</b>		
<b>Partition coefficient n-octanol/water (log Kow)</b>		
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER		-0,49
Butan-2-ol		0,61
<b>Bioconcentration factor (BCF)</b>	Not available.	
<b>12.4. Mobility in soil</b>	No data available.	
<b>12.5. Results of PBT and vPvB assessment</b>	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.	
<b>12.6. Endocrine disrupting properties</b>	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	
<b>12.7. Other adverse effects</b>	GWP: 0 The product contains volatile organic compounds which have a photochemical ozone creation potential.	
<b>12.8. Additional information</b>		
<b>Estonia Dangerous substances in soil Data</b>		
Butan-2-ol (CAS 78-92-2)		Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg Chemical pesticides (As the total sum of the active substances) 20 mg/kg Chemical pesticides (As the total sum of the active substances) 5 mg/kg

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

<b>14.1. UN number</b>	UN1950
<b>14.2. UN proper shipping name</b>	AEROSOLS
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-

Hazard No. (ADR) Not available.

Tunnel restriction code D

ADR/RID - Classification 5F  
code:

14.4. Packing group Not available.

14.5. Environmental hazards No

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### IATA

14.1. UN number UN1950

14.2. UN proper shipping name Aerosols

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

14.4. Packing group Not available.

14.5. Environmental hazards No

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### IMDG

14.1. UN number UN1950

14.2. UN proper shipping name AEROSOLS

14.3. Transport hazard class(es)

Class 2.1

Subsidiary risk -

14.4. Packing group Not available.

14.5. Environmental hazards

Marine pollutant No

EmS F-D, S-U

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments Not established.

ADR; IATA; IMDG



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Carbon dioxide (CAS 124-38-9)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

**Authorisations**

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Butan-2-ol (CAS 78-92-2)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Not listed.

**Other EU regulations**

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)

Butan-2-ol (CAS 78-92-2)

**Other regulations**

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

**National regulations**

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

**List of abbreviations**

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short-Term Exposure Limit.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

TWA : Time Weighed Average Value.

VLE: Exposure Limit Value.

VME: Exposure Average Value.

VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

**References**

Not available.

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.



**Full text of any H-statements  
not written out in full under  
Sections 2 to 15**

H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

**Revision information**

None.

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.